



Issued 22/09/2023



STREET TUNED

PRODUCT NEWS

TESLA MODEL Y 2020-

PART NO: TES MX00S1

Fits RWD & AWD models



Introducing the latest addition to our automotive range—the Öhlins Street Tuned line. Developed from our Road & Track line with a sharp focus on comfort, the new Street Tuned suspension offers an even more refined ride quality for daily driving without compromising vehicle handling and body control. The Öhlins Street Tuned suspension for Tesla Model Y is specifically designed to elevate driver comfort in battery electric vehicle (BEV) applications.

Adjustable damping control and ride height allow you to achieve the exact level of comfort and feedback you desire. The dampers are individually adjustable through a wide range of adjustment options, with more than 20 defined clicks for precise tuning. Systems feature a monotube damper structure designed for heightened responsiveness, with strengthened inverted struts and lightweight body shocks to aid in cooling.

Our new Street Tuned suspension package combines unparalleled ride comfort with premium features and tuning options, resulting in the ultimate comfort upgrade for Tesla Model Y. No matter your destination, the Öhlins Street Tuned dampers deliver a smoother ride with superior handling and control, ensuring a safer, more comfortable journey for you and your passengers.



GENERAL FEATURES

- > Designed for maximum ride comfort
- > Dual Flow Valve (DFV) technology
- > Rebuildable
- > Corrosion salt spray tested (ISO 9227)
- > 2 year limited warranty
- > Complete suspension kit with springs and accessories included

FRONT FEATURES

- > Conventional shock absorber
- > Single bleed adjuster
- > Spring preload adjuster
- > Height adjustable (0-10 mm lower than standard is recommended)
- > Coil springs (rate 70 N/mm)
- > Use with original top mounts

REAR FEATURES

- > Conventional shock absorber
- > Single bleed adjuster
- > Separate spring preload adjuster
- > Height adjustable (0-10 mm lower than standard is recommended)
- > Coil springs (rate 80 N/mm)
- > Use with original top mounts